Picture	Goods description	Configuration
XHUTI26	Vertical Machining Center XH7126	Siemens 808D control system, 3 axis linear rail, 12 umbrella type tools changer, full cover, BT40 8000rpm spindle
	Standard accessories	PRECISE BALL SCREW • LINEAR GUIDE •AUTOMATIC LUBRICANT •COOLANT • WORK LAMP CHUCK • WRENCH • WRENCH S21-24, • BLOCK, NUT AND WASHER • METAL COVER •TELESCOPIC COVER FOR 3 AXIS • PNEUMATIC CYLINDER AND TOOL CHANGER, • OPERATION MANUAL • A SET OF CUTTING TOOLS, 3-20 MM CUTTERS, 3/4/5/6/8/10/12/14/16/20, 2 EDGES AND 4 EDGES,3/4/5/6/8/10/12/14/16/20. I

All the detailed technical specifications are in followed pages:

Model: XH7126

Product picture



Product main technical specifications:

Specifications	Units	XH7126
Table size	mm	800x260
X axis travel	mm	500
Y axis travel	mm	320
Z axis travel	mm	450
Max. worktable load	kg	200
T slot(number-width-pitch)		3-14x80
Max. spindle speed	rpm	6000/8000

Product picture only for reference, technical updates without notice.

Spindle taper	mm	BT40
Main motor power	kw	3.7
X/Y/Z rapid traverse speed	m/min	15/15/15
X/Y/Z axis servo motor torque	Nm	6/6/7.7
Cutting feed speed	mm/min	1-6000
Guide rail type		Linear rail
Distance from spindle axis to column surface	mm	360
Distance between spindle nose and worktable surface	mm	90-470
Positioning accuracy	mm	±0.0015
Repeat positioning accuracy	mm	±0.0075
Tool magazine		12 armless
Max. tool diameter	mm	Ф90
Max.tool weight (ATC)	kg	8
Machine weight	kg	2400
Overall dimension	mm	2200×1900×2200

